



Stationary hydraulic Scissor Cargo & Car Lift

Stationary hydraulic scissor Cargo & Car Lift is a special use hydraulic table for cargo delivery at high levels of buildings. It is widely used for cargo delivery at workshops, warehouses and various isolated working layers and automobile lifts at high level for space and underground garages, etc. It is characteristic of its firm structure, great carrying capacity, various tables sizes, stable lifting, easy installation and convenient maintenance. Therefore, it can be a substitute for the elevator as an economic, useful and ideal cargo delivery equipment for cargo lift at lower floors.

- ◆ Installation flexibility. It can be installed at atrocious environment and general flameproof area.
- ◆ Wide range application. It is applicable for cargo delivery at high levels of most industries.
- ◆ Flexible configuration. Table size and entry and exit entrance location can be configured flexibly to meet various installation environment and demands.
- ◆ Relatively economi. It has relative lower price and maintenance free, and no special use machine is needed. construction budget can be, therefore, economized.
- ◆ Safe and reliable. Overload protection and pipe anti-crack safety valves for preventing table falling has been set up in hydraulic system to assure safe protection.
- ◆ Convenient operation. Control buttons can be set at all floors and tables to achieve multi-spots control.

Single Scissor Type

Type	Capacity	Travel	Max. height	Low height	Platform size	Rise time	Power	Whole weight
SJG2.5-2	2500	2000	2410	410	D3200XW2500	56	3	2300

Double Scissor Type

Type	Capacity	Travel	Max.height	Low height	Platform size	Rise time	Power	Whole Weight
SJG1-6	1000	6000		1230	D2200XW1500	70	2.2	2500
SJG2-6	2000	6000	1150		D2200XW2000	70	5.0	2800
SJG2-4.8	2000	4800	5500	700	D3600XW2000	40	4.0	3800
SJG2-5	2000	5000	5700	700	D4500XW2000	62	5.5	4000
SJG2.5-7.2	2500	7200	8030	830	D5200XW2500	95	7.5	8800
SJG3-4.5	3000	4500		1060	D2200XW1800	40	5.0	2200
SJG3-7.2	3000	4500	8060	860	D5500XW3000	90	7.5	8870
SJG5-5.4	5000	5400	6230	830	D5200XW2500	95	7.5	8000

Features:

- It is equipped with safety protection device to prevent lift tale from overloading.
- It is equipped with safety protection valve o prevent hydraulic pipeline from cracking.
- It is equped with emergent descending device in the condition of shut off.
- The descending speed can adjustable.



The hole of each floor size are platform size width +2X200mm & Depth+2X400mm.

