

Hydraulic Guide-type Elevator (Vertical Freight Lifts) CATALOGUE

Availabilities

Lifting height:1.65-20m; load capacity upto 30T(customer-made)
Warranty:12 months from delivery apart from artificial damage.

Advantages

1. Equipped single side or double sides hydro cylinder to keep the machinery works smooth and steady with noiseless, it is convenient and long working life.
2. safe manual operation in case of black out,emergence stop can give protection when some urgency happened.
3. the pit should be 15-30cm,the height of the top is unlimited.
4. custom made according to the multistoried building.
5. imported and domestic pump is optional.
6. Hydro-cylinder and sealing element adopt imported parts.
7. Imported controlling system is optional(Schneider,Siemens,etc)

Safety

Hydraulic elevators not only have all safety device of the traditional elevator,but also have the special safety system hereinafter.

1. Spillover valve, it can prevent high pressure when the machine moves up.
2. Manual emergency valve,it can go down to the nearest floor and open the door when you meet an emergency.
- 3.Pipe fracture valve,when the hydraulic system pipe fracture, it can cut down the channel of the oil to stop the falling.
- 4.Temperature protection, when the temperature of the hydraulic oil is substandard, the machine will stop working until the temperature reverts to the safe standard.

Hydraulic Guide-type Elevator (Vertical Freight Lifts) CATALOGUE

Projects shows:



Hydraulic Guide-type Elevator (Vertical Freight Lifts) CATALOGUE



Hydraulic Guide-type Elevator (Vertical Freight Lifts) CATALOGUE

Assembly parts:

